

2300°F / 1260°C: CerMax™ Ceramic Fiber Tape: Woven
Extreme High Temperature, Heat, Flame, Molten Metal & Weld Splatter Resistant



Available in Plain and Drop Warp style (also known as Ladder Tape™ or Bolt-Hole Tape).

Highly flexible and virtually no shrinkage. Melts above 3000°F / 1648°C.

Woven tape has the benefit of edges that will not fray unless cut.

Available with Fiberglass reinforcement or wire.

Common applications for this tape are as a gasket and seal material on high temperature access doors, inspection and clean-out doors and panels for kilns, ovens, furnaces, ventilation systems, etc.

CerMax™ Extreme Temperature +Plus, Heat, Flame, Molten Metal & Weld Splatter Resistant Ceramic Fiber Tapes						
Plain & Drop Warp Woven Tape – 100 foot roll						
Available in 1/16" / 2mm thick & 1/8" / 3.2mm thick						
Width inch / mm / dash #			Part Number	1/16" / 2mm Price per roll Fiberglass / Wire	1/8" / 3.2mm Price per roll Fiberglass / Wire	
1/2	13	-08	T-C-W-M013-08-X-Y	\$ 28.75 / NA	\$ 35.65 / NA	
1"	25	-16	T-C-W-M025-16-X-Y	\$ 43.70 / \$ 51.75	\$ 59.80 / \$ 66.70	
1 1/2"	38	-24	T-C-W-M038-24-X-Y	NA / NA	\$ 88.55 / NA	
2"	51	-32	T-C-W-M051-32-X-Y	\$ 78.20 / \$ 93.15	\$ 106.95 ** / \$ 124.20	
3"	76	-48	T-C-W-M076-48-X-Y	\$ 112.70 / \$ 117.30	\$ 154.10 ** / \$ 170.20	
4"	102	-64	T-C-W-M102-64-X-Y	\$ 141.45 / \$ 149.50	\$ 193.20 / \$ 218.50	
6"	152	-96	T-C-W-M152-96-X-Y	NA / NA	NA / \$331.20	

** Note: 1/8 thick 2" wide and 3" wide, fiberglass reinforced, is available in Plain or Drop Warp (also known as LadderTape™ or Bolt-Hole Tape). Same Price

This Product is Available in Full Rolls Only – Please enquire for exceptions

Some tapes available in 50 foot lengths – please enquire. Add 25% to above pricing when ordering in 50 foot lengths. Some tapes available in by-the-foot cut lengths – please enquire. Add 50% to above pricing when ordering by-the-foot cut lengths.

- For the "X" value, specify: "A1" for 1/16" thick tape or "B2" for 1/8" thick tape
- For the "Y" value, specify: "F" for Fiberglass reinforced or "W" for wire reinforced
 - Add "-DW" to specify Drop Warp style tape (Only in 2" and 3" widths).

To aid in mounting this tape onto surfaces, FlangeStik™ pressure sensitive adhesive spray can be used to place the tape in situ temporarily. Permanent fasteners or grab strips should be installed prior to heating of the area sprayed above 200°F. The adhesive will "smoke-off" at elevated temperatures.